

SOUTHERN UTE INDIAN TRIBE

Department of Energy

WELL SITE EQUIPMENT WORKSHEET

Applicant:		Permitter (if different than applicant):	
Well Name:		API #:	
Twn:	Rng:	Section:	Quarter/Quarter:
FACILITIES:	NUMBER OF FACILITIES:	HORSEPOWER:	ELECTRIC/GAS DRIVEN:
Wells : _____	_____	_____	_____
Drilling Pits: _____	_____	_____	_____
Pump Jacks: _____	_____	_____	_____
Gas or Diesel Motors: _____	_____	_____	_____
Dehydrator Units: _____	_____	_____	_____
Oil Tanks: _____	_____	_____	_____
Production Pits: _____	_____	_____	_____
Separators: _____	_____	_____	_____
Electric Motors: _____	_____	_____	_____
Vapor Recovery Unit: _____	_____	_____	_____
Condensate Tanks: _____	_____	_____	_____
Special Purpose Pits: _____	_____	_____	_____
Injection Pumps: _____	_____	_____	_____
Electric Generators: _____	_____	_____	_____
VOC Combustor: _____	_____	_____	_____
Water Tanks: _____	_____	_____	_____
Multi-Well Pits: _____	_____	_____	_____
Cavity Pumps: _____	_____	_____	_____
Fuel Tanks: _____	_____	_____	_____
Flare: _____	_____	_____	_____
Buried Produced Water Vaults: _____	_____	_____	_____
Modular Large Volume Tanks: _____	_____	_____	_____
Gas Compressors: _____	_____	_____	_____
LACT Unit: _____	_____	_____	_____
Pigging Station: _____	_____	_____	_____
Southern Ute Tribal Well Pad Requirements:			
1) Notification to DOE is required, if any equipment is removed or added to the wellsite – kspray@sudoe.us			
2) Any venting or flaring of a well shall be reported to SUIT-DOE as soon as it is known that venting or flaring will be utilized. SUIT-DOE will provide instructions to the company for notification to homeowners, if necessary – kspray@sudoe.us			
3) Sound emission will be in accordance with COGCC Rule 800 Series and Southern Ute Tribal requirements;			
4) No construction shall take place if there is inclement weather conditions that would create more than 3-inch ruts, such as, snow on the ground, raining or wet conditions, etc. (SEE General Well Pad Stipulations)			
5) Operator shall electrify any production equipment which is located within ¼-mile of a 3-phase electric line;			
6) Outdoor lighting fixtures with an initial output of more than 2,000 lumens shall have a full cutoff fixture & designed to shield the source of illumination from view;			
7) Operator/Contractor shall remove chains from heavy equipment before entering a public road; mud or debris tracked onto a public road shall be removed;			
8) All access roads and well pads with be constructed and maintained in accordance with generally accepted standards for repair, orderliness, neatness, sanitation, and safety. (SEE General Well Pad Stipulations)			
COMMENTS:			